



Electrical characteristics:

Power supply : 230VCA
Consumption: 15W – 15VA
Power lamp xenon 5; 15; 21 Joules (depending on model)
Frequency of flash: 60/min
Sound signal: 90 - 110 dB at 1 m.
Telephone relay: electronical telephone relay integrated
Telephone current: 30 to 100Vac 25-50 Hz
Impedance on telephone line: >3.5 KOhm
Signal volume modifiable: 1 or 2 tons, treble or basse

Mechanical characteristics:

Weatherproof protection: IP 66
Painting: special protection painting
Made of aluminium
Color : RAL2003 (orange)
Mounting: on wall or on pillar
Connection to telephone : on special integrated connector
Cable glands : 2 (supplied not mounted)

Cable gland : for cable from Ø6 to Ø8 mm
Glass of flash lamp: Polycarbonate transparent (IK09)
Cable type : cable with maximum section 1.5mm²
Dimensions: 193 X 223 X 432 mm
Weight: 7.6 kg
Temperatures of use : - 55°C / +70°C
EX marking : in the EX certificate (depends on model)
EAC marking : in the EAC certificate (depends on model)

Options:

- other colors
- different possible colors of the lamp glass
- 3 cable entries
- possible power supply 24-48 VDC

Other documents:



This equipment is under warranty during 2 years after delivery