

XPP-5454G

Intrinsically Safe Multi-Function Dual-Light™ Headlamp

MARKET APPLICATIONS

Hazardous work environments, industrial, automotive, law enforcement, fire & rescue

DESCRIPTION

This non-rechargeable multi-function Dual-Light[™] headlamp is cETLus, ATEX, IECEx and INMETRO listed Intrinsically Safe. This headlamp features a multi-position tilt head design and includes an elastic head strap with a non-slip lining and a heavy-duty rubber head strap for use on a hard hat. The dual top mounted switches provide user-selectable high or low-brightness spotlight, high or low-brightness floodlight operation and our exclusive Dual-Light design... the ability to turn on both the spotlight and the floodlight at the same time for maximum user safety and lighting versatility. Power comes from 3 AAA premium batteries (included).

CASE MATERIAL Engineered Polymer - Green

DIMENSIONS Width: 2.6 inches (66 mm) • Height: 2.1 inches (53 mm) • Depth: 1.8 inches (46 mm)

WEIGHT Weight: 3.3 oz. (94 g) with batteries installed

LIGHT SOURCE

Unbreakable polycarbonate with scratch resistant coating
CREE® LED Impervious to shock with a 50,000 hour lifetime

LIGHT OUTPUT High-Brightness Spotlight: 115 lumens • Low-Brightness Spotlight: 60 lumens • High-Brightness Floodlight: 120 lumens

• Low-Brightness Floodlight: 60 lumens • Dual-Light: 160 lumens

ON/OFF Dual Switches. High/Low Spotlight, High/Low Floodlight, Dual-Light

RUN-TIME High-Brightness Spotlight: 5 hours • Low-Brightness Spotlight: 16.25 hours • High-Brightness Floodlight: 4.25 hours •

Low-Brightness Floodlight: 13.75 hours • Dual-Light: 3.5 hours

BATTERY 3 Alkaline AAA batteries (included)

• cETLus, ATEX, IECEx and INMETRO listed Intrinsically Safe

• CREE® LED technology – 50,000 + hours LED life

High/low-brightness spotlight, high/low-brightness floodlight
 & Dual-Light™


- · Focused spotlight beam for distance illumination
- · Wide unfocused floodlight beam for close-up illumination
- · Engineered polymer housing
- Dual switches located on top of light
- Adjustable ratchet tilt head
- Non-slip elastic head strap
- · Heavy-duty rubber strap for hard hat applications
- Waterproof
- · Impact & chemical resistant
- Powered by 3 premium AAA alkaline batteries (included)

| FL1 STANDARD | DUAL-LIGHT | HIGH | LOW |
|--------------|---------------|---------------|--------------|
| 314 | 160 LUMENS | 115 LUMENS | 60 LUMENS |
| 0 | 3h 30min | 5h | 16h |
| M | 94m | 82m | 60m |
| | 1711cd | 1668cd | 882cd |
| 2m | | | |
| 1m | | | |

WARRANTY

Limited Lifetime Warranty • Includes the LEDs, housing and lenses. Rechargeable batteries, chargers, switches, electronics and included accessories are warranted for a period of two years with proof of purchase. Disposable, non-rechargeable batteries are excluded from this warranty. Normal wear and failures which are caused by accidents, misuse, abuse, faulty installation and lightning damage are also excluded.

APPROVALS



Nightstick 5454 Headlamp

c Usteo US

ID 4008947
INTRINSICALLY SAFE
SECURITE INTRINSEQUE



Intertek

CLASS | DIV 1 GRPS A-D T3 CLASS || & III GRPS E-G T135C CLASS | ZONE 0 AEx ia IIC T3 Ga CLASS | ZONE 0 Ex ia IIC T3 Ga © II 1 G Ex ia IIC T3 Ga

Ex ia IIC T3 Ga
Intertek ITS 13 ATEX27928X
IECEx ETL 13.0045X
-20°C ≤ Tamb ≤ +40°C
1.5V/Cell AAA Alkaline

C € 0359

5:00

Conforms to:

ANSI/UL STD 913, ANSI/UL 60079-0, ANSI/UL 60079-11 ANSI/ISA 60079-26 CAN/CSA STD C22.2 No 157 CAN/CSA STD C22.2 No 60079-0 CAN/CSA STD C22.2 No 60079-11 CSA STD C22.2 No 25

Certified to:

Designed in USA, manufactured in China at a ISO-9001 certified Bayco facility.